

# Dust Magnet

# Changes the electromagnetic properties of dust for a lasting clean.

#### The Prescription for Chronic Dust

Our proprietary, positively charged formulation causes dust to clump and fall preventing its accumulation. Once treated, dust is easily swept and disposed of, thereby reducing the time of routine cleaning significantly. Use at only a few ounces at a time.

## Straightforward Packaging

We use simple, straightforward packaging, investing instead in advanced formulation technology. Our containers are easily used in conjunction with inexpensive metering equipment and dispensers.

## **Advanced Concentration**

All of our products are concentrated to the highest practical level. Dust Magnet is used at only a few ounces per cleaning. One gallon will cover over 3000 square feet.


Directions: Dust Magnet works by neutralizing the static charge on dust particles of all kinds. Once the charge is neutralized, the particles will naturally stick together. No oily sawdust needed, no slick and shiny floors, and no dust swirling into the air.

Fill a pump-up sprayer with Dust Magnet, adjust the tip to the finest spray possible, and then lightly mist the floor before sweeping. That's it! Don't over-apply. The floor should not look obviously wet when finished spraying. One gallon should cover about 3 ,000 square feet.

Be sure to reapply Dust Magnet after sweeping. This will keep the dust out of the air for at least a week. Maintenance application of Dust Magnet, except in extremely dusty environments, is generally more effective if done directly after sweeping.

Caution: Although Dust Magnet is non-flammable and no adverse health effects are expected from incidental exposure, normal industrial hygiene habits should be followed.

Keep this and similar materials out of the reach of children.



Hazard Statements H320 Causes eye irritation.

Aleva Chemical 1792 Latham Street Memphis, TN 38106 Toll-Free: 1-888-504-8178 AlevaChem.com Info@Alevachem.com Classification of the substance or mixture OSHA HCS 2012 Mild Irritant (Skin) Eye Damage/Irritation 2B (Irritant) Label Elements OSHA HCS 2012 Prevention P264 Wash hands and skin after handling.

<b>7</b> Neutral	Surface Type	Coverage	Ready to Use
	Floors	30 ft <sup>2</sup> / oz	Formula